

SM 57-2



The compact and rugged pavement saws of the SM-57-2 series are ideal solutions for daily cutting work. Thanks to their powerful engines, they allow quick and efficient cutting down to a depth of 120 mm (4.7 in.).

Technical details

- ▶ Indicator scale for cutting depth with preset device
- ▶ Water tank
- ▶ Water splash guard
- ▶ Quick adjustment with foot lock
- ▶ Air intake located outside the dust zone above the water tank

Technical data SM 57-2

Type		SM 57-2	SM 57-2 Hd
Service weight with empty tanks	kg (lbs)	65 (143)	65 (143)
Service weight as per CECE	kg (lbs)	70 (154)	70 (154)
Blade diameter	mm (in.)	350 (13.8)	350 (13.8)
Diameter of blade aperture	mm (in.)	25.4 (1.0)	25.4 (1.0)
Max. cutting depth	mm (in.)	120 (4.7)	120 (4.7)
Cutting blade speed	r.p.m.	3,150	3,150
Engine manufacturer		Robin EH 25 D	Honda GX 270
Engine type		4-stroke, gasoline	4-stroke, gasoline
Engine power output, max.	kW (HP)	6.3 (8.5)	6.0 (8.2)
Power output at operating speed	kW (HP)	4.7 (6.4) at 3,600 r.p.m.	5.1 (7.0) at 3,600 r.p.m.
Type of drive		manual	manual

We reserve the right to alter specifications.

Technical features SM 57-2

Indicator scale for cutting depth
Water tank, 8-litre (2.1 gal)
Water splash guard
Quick adjustment with foot lock
Lifting possibility/guide bar/recessed grip/handle
Air intake located outside the dust zone above the water tank

Saw blade is sold separately.